



Single Ended Halogen ot CP83 240V 10000W BX 1/1 MIJ **12037**

Product information

Quartzline® lamps designed for optimum performance in today's precision range of stage, studio and architectural luminaires. Full range up to 24,000 W -Range of bases to meet the needs of OEMs -Chromised seal protection up to 500° C.


Application areas



() Theatre











Product data

12037
Tubular
85
405
508
1383
General Electric (GE)
G38

Performance data

Weighted energy consumption [kWh/1000h]	9777.33
Energy efficiency class (EEC)	С
Rated Life [h]	500
Nominal correlated colour temperature (CCT) [K]]	3200
Nominal lumens [lm]	280000

Electrical data

Coil type	CC-8
Dimming Capability	Yes
Ballast Required	Yes
Nominal power [W]	10000
Nominal lamp voltage [V]	240





Logistic data

DUN Code	20043168120375
EAN Code	0043168120371
Pack Quantity	1
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	20 EUR, 25 UK
Layer quantity EUR	20
Layer quantity UK	25
Pallet quantity EUR (PC)	20
Pallet quantity UK (PC)	25
Outer case size	200 x 205 x 540 (mm)
Product status	Available

Downloads & Links Go to the catalog site (HTTP) Entertainment Solution Spectrum Catalogue (PDF) Lighting design tools & calculators (HTTP) Entertainment Solution Spectrum Catalogue (PDF) Lighting design tools & calculators (HTTP) High-res images / Technical drawings (HTTP) Certificate for the Quality Management System of GE Lighting EMEA (PDF) Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

Disclaimer

Special Purpose Lamp, Not suited for household illumination