

DSN 30 Dowel fastening nail 30320



Areas of application:

Conduit installations: Affixing cable ducts, for smoke detectors and small lamps with the DSN.

Installation Guide:

- Drill a 6 mm Ø hole
- Put Dowel Fastening Nail through a hole of the item to be fixed and push the DSN into the drill-hole.

Product details:

Colour:	light grey
Content pack/box	200 / 10.800
Nail length in mm	31


Product benefits/properties:

Very good clamping effect thanks to nail heads special shape. No dowels or screws required. All products are for 01 - 20 mm material thickness suitable for E0 cables. The Dowel Fastening Nails DSN 30 and DSN 40 are, due to their slim width of only 4.5 mm, suitable for time and effort saving mounting of fire detectors, lamps and many other objects in slotted holes.

Technical data:

Material	PA 6, UV stabilised Temperature range: -20 °C up to +85 °C silicon-free halogen-free
Weight per piece	0,70 g
Max. recd. load	Reference value: DSN30: 200 N (20 kg) concrete, 200 N (20 kg) solid brick, 150 N (15 kg) hollow brick, 50 N (5 kg) aerated concrete, 70 N (7 kg) plasterboard 25 mm
Breaking load	Reference value: DSN30: 340 N (34 kg) concrete, 330 N (33 kg) solid brick, 310 N (31 kg) hollow brick, 75 N (7.5 kg) aerated concrete, 85 N (8.5 kg) plasterboard 25 mm

GTIN (EAN)



With the DSN 30 und DSN 40 you will successfully fasten fire detectors, lamps and sockets at the push of a thumb.

Schnabl Stecktechnik GmbH
Bahnhofplatz 1, Postfach 63, 3100 St. Pölten, Austria
Telefon +43(0)2742/22167-0, Telefax +43(0)2742/22167-50
office@schnabl.works, www.schnabl.works

 **Schnabl**[®]
time saving products

Stand: 2/2020