

ESD 30 Euro fastening anchor 31300



Areas of application:

Pipe Fixing: The ESD fits into a 6 mm diameter drilled hole and is the clip on fixing for the Schnabl EC Euro clip. It is suitable for use on Plasterboard/fermacell, concrete, bricks, thermalite and breeze blocks.

Installation Guide:

EC in combination with an ESD:

- Drill a 6 mm Ø hole
- Click the EC to the ESD and insert both into the drill-hole
- The EC clamp is adjustable after mounting to the ESD
- Push the pipe into the clamp
- Cables can be attached to the ESD with a cable tie

Product details:

Colour:	light grey
Content pack/box	100 / 4.800
Length in mm	27


Product benefits/properties:

The basic principle of Schnabl fastening technology centres around the insert able clip - no plug or screw is required - inserted into a 6 mm drilled hole. When the ESD is inserted into the drilled hole, the eccentric tine pairs along the plastic shaft form a friction connection with the wall of the hole which increases in torque force as the load increases! Simply remove by unscrewing.

Technical data:

Material	PA 6, UV stabilised Temperature range: -20 °C up to +85 °C silicon-free halogen-free
Weight per piece	1,10 g
Max. recd. load	Reference value: ESD 30: 250 N (25 kg) concrete, 225 N (22.5 kg) solid brick, 230 N (23 kg) hollow brick, 100 N (10 kg) aerated concrete, 150 N plasterboard 25 mm
Breaking load	Reference value: ESD 30: 359.00 N (35.9 kg) concrete, 325.50 N (32.5 kg) solid brick, 335.70 N (33.5 kg) hollow brick, 151.30 N (15 kg) aerated concrete, 225.60 N (22.5 kg) plasterboard 25 mm

GTIN (EAN)



The perfect combination: ESD Euro-fastening anchor and EC Euro-clip for efficient pipe fixing.

Schnabl Stecktechnik GmbH
Bahnhofplatz 1, Postfach 63, 3100 St. Pölten, Austria
Telefon +43(0)2742/22167-0, Telefax +43(0)2742/22167-50
office@schnabl.works, www.schnabl.works

Stand: 2/2020

 **Schnabl**[®]
time saving products