

# TB 10 Terrace bracket 33050

CE

## Areas of application:

For the chased fixing of sheathed cables, flexible tubing and conduits, on and under plasterboard.

## Installation Guide:

- Drill a 6mm Ø hole
- Insert the TA in the drill-hole
- Click the TB onto the TA
- Put flexible pipes under the TB
- Push the TB tight with your thumb
- Cut the end points of the TB to the desired size

## Product details:

Colour:	light grey
Content pack/box	50 / 1.000
Clamping range in	100

## Mounting and usage instructions:

The TB is fixed to the TA support anchor. Several TBs can be fixed to one TA. The fixing of the TBs can be done in several stages.

## Product benefits/properties:

The TB provides a secure hold even with different conduits/cables dimensions. Fast cable placement with no plastering.

## Technical data:

Material	POM, UV stabilised Temperature range: -20 °C up to +100 °C silicon-free <b>halogen-free</b>
----------	--

Weight per piece 5,60 g

GTIN (EAN)



*With the TB in two sizes, Schnabl has in combination with the TA a system for all requirements - on or under plasterboard*



Schnabl Stecktechnik GmbH  
Bahnhofplatz 1, Postfach 63, 3100 St. Pölten, Austria  
Telefon +43(0)2742/22167-0, Telefax +43(0)2742/22167-50  
office@schnabl.works, www.schnabl.works

Stand: 2/2020

 **Schnabl**<sup>®</sup>  
time saving products