

General info

DECORATIVO - Ceiling

Indoor ceiling or wall mounted lamp with integrated LED sources and diffuse light emission

Powder coated metal base. White acid-etched blown glass diffuser with fastening system without screws. Easily replaceable integrated led source.

Ean	8021696261164
Item	LEVEL PL D40
Installation	Ceiling
Guarantee	5 years
Gross weight	3.4 kg
Volume	0.054121 m ³

Technical info

Net weight	2.36 kg
Insulation class	II
Protection index	IP20
Compliance	-
Operating temperature	0° ~ +40 °C
Dimmer	No dimmerable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included YES (by qualified operators only), electronic

Source info

Integrated source	Integrated LED module
Replaceable source	YES (by qualified operators only)
Power	LED 22,5W
Emission	Diffuse
Max consumption	max 22,50 W
Features LED	LED SMD module
CCT	3000 K
Duration LED (t. 25°C)	17500 h
CRI	> 80
Light beam flux	2100 lm
Useful light flux	1900 lm
Standby power	< 0.50

General info

DECORATIVO - Ceiling




Indoor ceiling or wall mounted lamp with integrated LED sources and diffuse light emission

Powder coated metal base. White acid-etched blown glass diffuser with fastening system without screws. Easily replaceable integrated led source.

Ean	8021696261188
Item	LEVEL PL D60
Installation	Ceiling
Guarantee	5 years
Gross weight	7.14 kg
Volume	0.1122 m ³

Technical info

Net weight	5.12 kg
Insulation class	II
Protection index	IP20
Compliance	-
Operating temperature	0° ~ +40 °C
Dimmer	No dimmerable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included YES (by qualified operators only), electronic



Source info

Integrated source	Integrated LED module
Replaceable source	YES (by qualified operators only)
Power	LED 37,5W
Emission	Diffuse
Max consumption	max 37,50 W
Features LED	LED SMD module
CCT	3000 K
Duration LED (t. 25°C)	17500 h
CRI	> 80
Light beam flux	3300 lm
Useful light flux	2950 lm
Standby power	< 0.50