

# Cover HS-22

Ref. B17011



- Recommended for the construction of sealed lighting fixtures

## APPLICATION

- LED protection and light diffusion in lighting fixtures


## MOUNTING

- to the profile, by pressing

## ADDITIONAL INFORMATION

- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance  $\pm 1.5$  mm) and 2005 mm / 3010 mm (tolerance  $+ 5$  mm); for selected covers: 6050 mm, 10050 mm (tolerance  $+ 5$  mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

## TECHNICAL DRAWING



## TECHNICAL SPECIFICATIONS

|                        |      |
|------------------------|------|
| Shape                  | flat |
| Possibility of bending | yes  |
| UV resistance          | yes  |

| Finish     | Material | Maximum length on request | Light transmission | Length  | Width   | Possibility of obtaining a line of light | Ref       |
|------------|----------|---------------------------|--------------------|---------|---------|------------------------------------------|-----------|
| frosted    | PC       | 3000 mm                   | 65 %               | 1000 mm | 21 mm   | yes                                      | B17011F_1 |
|            |          |                           |                    | 2005 mm |         |                                          | B17011F_2 |
|            |          |                           |                    | 3010 mm |         |                                          | B17011F_3 |
| clear      | PC       | 3000 mm                   | 88 %               | 1000 mm | 21 mm   | no                                       | B17011C_1 |
|            |          |                           |                    | 2005 mm |         |                                          | B17011C_2 |
|            |          |                           |                    | 3010 mm |         |                                          | B17011C_3 |
| microprism | PMMA     | 3050 mm                   | 90.5 %             | 1000 mm | 23.6 mm | no                                       | B17011M_1 |
|            |          | 3010 mm                   |                    | 3010 mm |         |                                          | B17011M_3 |

## RELATED PROFILES > ARCHITECTURAL



**DIPOK-US**  
A01233



**DIPOKET**  
A01177



**GIZA**  
A05556



**GIZA-DUO-LL**  
A02162



**GIZA-LL**  
A00758



**GIZA-LL-T**  
A02479



**GIZA-LL-UST**  
A02724N



**GLAZA-DUO**  
A03059



**KOZEL**  
A06454




**KOZUS**  
A07823



**KOZUS-CR**  
A00600



**LARKO**  
A05552



**LIPOD**  
A05554



**LOC-30**  
A18015




**LOKOM**  
A05553



**OPAC-30**  
A06164

## RELATED PROFILES > FACADE



**FASKO**  
A04323

# Cover HS-22

Ref. B17011

## RELATED PROFILES > FOR BUILDING WALL LAMPS AND ILLUMINATING WALLS



**KIDES-DUO**  
A18032



**WERKIN**  
A18025

## RELATED PROFILES > STAIRS ILLUMINATION



**STEPUS**  
A18038