

BTLW LED

Track light projector



[V] 220-240 AC	[Hz] 50	≥30000	[h] 50000	ellipse ≤ 6x MacAdam	Ra 90	COB
		IP 20		[°C] 5+25		[°] 340
[°] 90	0,5m					



BTLW 18W-930-W



	[W]	[lm]	Tc [K]	[°]		
BTLW 18W-930-W	35662	18	1450	3000	120	white
BTLW 18W-930-B	35663	18	1400	3000	120	black
BTLW 18W-940-W	35664	18	1450	4000	120	white
BTLW 18W-940-B	35665	18	1400	4000	120	black

Kanlux BTLW LED is a new design of luminaires adapted to the Kanlux TEAR rail system and to the majority of 3-circuit rail systems. Luminaires are equipped with a power supply integrated with the adapter. Kanlux BTLW are characterized by a milky lamp diffusing light, providing a wide viewing angle of 120°. They are available in 18W, two housing colors (white or black) and two light colors. They are perfect for home conditions, as general lighting and wherever a wide lighting beam angle of the luminaire is needed

- 5 years Warranty under the terms of the warranty statement, available on our website
- Enclosure material: aluminum alloy

BTLW LED

Track light projector



BTLW 18W-930-W




BTLW 18W-930-B




BTLW 18W-940-W




BTLW 18W-940-B




BTLW 18W-930-W



BTLW 18W-930-B



BTLW 18W-940-W



BTLW 18W-940-B