

MAA1035Y10



OTL35 gnybtas 1xAl/Cu 2,5-35mm² 1000V AC / 1500V DC g/ž

OTL35 gnybtas 1xAl/Cu 2,5-35mm² 1000V AC / 1500V DC g/ž

|                 |                         |
|-----------------|-------------------------|
| Prekės kodas    | MAA1035Y10              |
| EAN             | 4744397013804           |
| ETIM klasė      | EC000897                |
| Gaminių serija  | Universal terminals OTL |
| CN8 kodas       | 85369010                |
| Vienetas        | vnt                     |
| Pakuotės dydis: | 54                      |
| Svoris (neto)   | 0.027 kg                |
| Ilgis           | 0.045 m                 |
| Plotis          | 0.016 m                 |
| Gylis           | 0.04 m                  |

|                                                                          |                               |
|--------------------------------------------------------------------------|-------------------------------|
| Connectable conductor cross section fine-strand without cable end sleeve | 2.5 - 25 mm²                  |
| Connectable conductor cross section fine-strand with cable end sleeve    | 2.5 - 25 mm²                  |
| Connectable conductor cross section solid-core                           | Nežinoma                      |
| Connectable conductor cross section multi-wired                          | 2.5 - 35 mm²                  |
| Rated current In                                                         | 135 A                         |
| Rated voltage                                                            | 1500 V                        |
| Type of electrical connection 1                                          | Screw connection              |
| Type of electrical connection 2                                          | Netaikoma                     |
| Number of levels                                                         | 1                             |
| Number of clamp positions per level                                      | 2                             |
| Suitable for conductor material                                          | -                             |
| Mounting method                                                          | DIN rail (top hat rail) 35 mm |
| Material insulation body                                                 | Thermoplastic                 |
| Operating temperature                                                    | -25 - 80 °C                   |
| Inflammability class of insulation material according to UL94            | V0                            |
| Width                                                                    | 16 mm                         |
| Height                                                                   | 40 mm                         |
| Depth                                                                    | 45 mm                         |
| Explosion-tested version 'Ex e'                                          | Ne                            |
| Closing plate required                                                   | Ne                            |
| Colour                                                                   | Green/yellow                  |
| Internally connected stages                                              | Taip                          |

