

Technical data sheet

Push-fit plug Delta-Push® for pushing in

Item number: 2351670



Push-fit plug Delta-Push® for mounting electrical installations. Suitable for concrete, calcareous limestone, full brick, hollow brick and porous concrete. Toolless mounting by pushing into a drill hole in a wall or on a ceiling. Without screws. To install cable trunking or labelling panels, for example.



PA Polyamide

Master data


Item number	2351670
Type	DP D 30
Description 1	Push-fit plug
Description 2	for pressing in
Available from	01.02.2025
Manufacturer	OBO
Dimension	34,2x14,2x12,2
Material	Polyamide
Smallest sales unit	100
Unit of quantity	Piece
Weight	0.083 kg
Weight unit	kg/100 pc.

Technical data sheet

Push-fit plug Delta-Push® for pushing in

Item number: 2351670



Dimensions		
	Length	30 mm

Technical data		
	Version for	Push-fit anchor
	Drill hole depth	35 mm
	Drill hole diameter, min.	6 mm
	Suitable for fastening with cable ties	no
	Suitable for gas concrete	yes
	Suitable for hexagonal wood screw	no
	Halogen-free	yes
	With edge	no
	With bolts	no
	Suitable for material	Calcareous sandstone Porous concrete Concrete Gas concrete Full brick Hollow brick
	Mounting type, anchor, tie	Push-through mounting