




|                                 |            |
|---------------------------------|------------|
| Mounting                        | Ceiling    |
| Voltage (V)                     | 100V-240V  |
| Hertz                           | 50/60Hz    |
| Class                           | II         |
| IP                              | 20         |
| Power (W)                       | 8          |
| Light source                    | GU10 LED   |
| Light source included           | No         |
| Socket included                 | No         |
| Number of lamp holders          | 2          |
| Tilt angles                     | 60         |
| Structure material              | Steel      |
| Structure finish                | Matt White |
| Cut-out Size for Recessed Mount | 83x165     |
| Maximum Ceiling Thickness (mm)  | 24         |



Installation instructions



Recommended bulbs



| GU10 LED              |           |
|-----------------------|-----------|
| Reference             | 17316     |
| Voltage (V)           | 220V-240V |
| Hertz                 | 50/60Hz   |
| Power (W)             | 7         |
| Luminous Flux (lm)    | 632       |
| Color temperature (K) | 2700K     |



| GU10 LED    |           |
|-------------|-----------|
| Reference   | 17320     |
| Voltage (V) | 100V-240V |
| Hertz       | 50/60Hz   |

Related accessories



| Lampholder GU10    |       |
|--------------------|-------|
| Reference          | 43065 |
| IP                 | 20    |
| Structure material | Steel |