



CD426J

**RCCB 4P 25A 30mA AC**

Technische Merkmale

**Architecture**

Neutral position	right
Number of poles	4 P
Fixing mode	Din-Rail

**Main electrical features**

Rated operational voltage Ue	230/400 V
Frequency	50 Hz

**Voltage**

Rated insulation voltage	500 V
Rated impulse withstand voltage	4 kV

**Electric current**

Rated residual operating current	30 mA
Surge current strength (waves 8/20µs)	0,25 kA
Breaking and opening capacity	1,5 kA
Rated conditional short-circuit current Inc according to EN 61008-1	6 kA

**Electric current / temperature**

Rating current -15°C	25 A
Rating current -20°C	25 A
Rating current 0°C	25 A
Rating current 10°C	25 A
Rating current -10°C	25 A
Rating current 15°C	25 A
Rating current 20°C	25 A
Rating current 25°C	25 A
Rating current -25°C	25 A
Rating current 30°C	25 A
Rating current 35°C	25 A
Rating current 40°C	25 A
Rating current 45°C	25 A
Rating current 5°C	25 A
Rating current -5°C	25 A
Rating current 50°C	25 A
Rating current 55°C	25 A
Rating current 60°C	25 A
Rating current 65°C	22 A
Rating current 70°C	18 A

## Power

Total power loss under IN	4,5 W
Power loss per pole at In	2 W

## Tripping

Short-time delayed tripping	No
-----------------------------	----

## Endurance

Electric endurance in number of cycles	2000
Number of mechanical operations	4000

## Dimensions

Depth of installed product	70 mm
Height of installed product	83 mm
Width of installed product	70 mm
Construction size (DIN 43880)	1

## Installation, mounting

Tightening torque	2,8Nm
-------------------	-------

## Connection

Connection cross-sect. flexible cable	16mm <sup>2</sup>
Connection cross-sect. rigid cable	25mm <sup>2</sup>
type of connection	with screw

## Equipment

Can be accessorized	Yes
---------------------	-----

## Standards

Standard text	IEC 61008-1, EN 61008-1
European directive RoHs	voluntary compliance
European directive WEEE	not concerned

## Safety

Protection index IP	IP20
Residual current type	AC

## Use conditions

Degree of pollution according to IEC 60664 / IEC 60947-2	2
Altitude	2000 m
Storage temperature	-55 to 70 °C