

EUTRAC 3-PHASE RECESSED TRACK

high-voltage track, white, 2 m



Article number	145211
Feed-in capability	No
Lamp included	No
Installation width	4 cm
Length	200 cm
Width	5.9 cm
Height	4.1 cm
Net weight	2.348 kg
Gross weight	3.334 kg
Material	Aluminium/plastic
Colour	white
Way of mounting	Recessed ceiling mounting
Remark 1	Maximum load 16A
Remark 2	The angle bracket is limited to a maximum load of 4 kg per meter
Remark 3	VDE and ENEC tested
remark5	Flexible suspension on spring clips over arrow-shaped profiling
Catalogue page	BIG WHITE 2018: 480
form	square

Articles of this series

145311	EUTRAC 3-PHASE RECESSED TRACK, high-voltage track, white, 3 m
145541	FEED-IN for EUTRAC 240V 3-phase recessed track, earth electrode left, white
145551	SPRING CLIP for EUTRAC 240V 3-phase recessed track, 6-pack
145571	LONG CONNECTOR for EUTRAC 240V 3-phase recessed track, electrical / mechanical, white
145621	END CAP for EUTRAC 240V 3-phase recessed track, white
145751	L-CONNECTOR for EUTRAC 240V 3-phase recessed track, white, earth electrode inside
145761	L-CONNECTOR for EUTRAC 240V 3-phase recessed track, white, earth electrode outside
145771	FEED-IN for EUTRAC 3-phase high-voltage recessed track, white, earth electrode right

Aluminium carrier track of the EUTRAC 240V 3-circuit recessed track system. The surface-mounted version of this system is available in several lengths. The special design makes it possible for ceiling panels to be put onto the rail itself. For more detailed information about the maximum load, please refer to the instructions in the manual. Alternatively, there is a surface-mounted version available too. Please note that the white tone will be changing from RAL 9010 to RAL 9016 (traffic white) on 1st April 2018. More information can be found under Product Information in the "Service" / Downloads area.

Notes
